

# 600MM DIA DEEP INSPECTION CHAMBER

## Product Data Sheet

600mm deep inspection chamber as a single piece system, suitable for adoptable and non-adoptable applications.

### PRODUCT CODE - PIC60016020

Nominal Diameter | 600mm

Main Inlet and Outlet | 160mm

Side Branches | 4 side branch inlets

- 2 x 110mm x 45°

& 2 x 160mm x 90°

*\*Available in 110mm pipework & 150mm Twinwall pipework*

### Application

- Maximum installation depth - adoptable 2.0m and non-adoptable 3.0m
- For aboveground access and maintenance inspection of buried pipework up to 3 metres deep
- For pedestrian use - granular backfill
- For vehicle use - concrete backfill

### Key Benefits

- Shaft units can be cut to required length
- Lightweight [no heavy lifting]
- Ready to install with no assembly required
- Manufactured in the UK
- Restrictor caps are available for chambers deeper than 1.2m

### Compliance

- DCG 2020 Chamber Detail - Type D & E
- Sewers for Adoption [SfA7] 7<sup>th</sup> Edition
- Building Regulations - Part H1



Tested to BS EN 13598-2 & conforms to building regulations



Installation guidance and assistance is available  
For further information, please call 0121 552 8887

info@polydraincivils.com | www.polydraincivils.com

